

SUF-FIX MITRE FAST ADHESIVE (ACTIVATOR & GLUE)

1 – DESCRIPTION

SUF-FIX Mitre is an adhesive set consisting of high viscosity cyanoacrylate and activator, which is developed especially for bonding materials such as UPvc ,Glass, Rubber ,natural stone, marble decorative stones.

2 – PROPERTIES

- Ability to bond rapidly in seconds,
- After Cured Its transparent and not change colour on the surfaces
- Suitable for use on vertical surfaces as it will not drip or slump.
- Activator makes it possible and incredibly fast to bond even porous surfaces,

3–APPLICATIONS

- Utilized in assembly and repairs of parts such as natural stone, marble, granite, wood, MDF and metal,
- Especially suitable for the applications where cure speed needs to be accelerated.
- Although Suf-Fix Mitre fast Adhesive has a degree of gap filling ability, it is generally recommended for use on close-fitting parts and fairly smooth, even surfaces.

4 –INSTRUCTIONS

Substrates need to be smooth and have a perfect connection area. Apply a drop on one of the substrates. Join substrates and press firmly for one minute. Application temperature is between +5°C and +35°C.

5–PACKAGING

Product	Volume/Weight	Package
Activator & Glue	200 ml + 65 gr	24
Activator & Glue	200 ml +50 gr	24
Activator & Glue	400 ml + 125 gr	24
Activator & Glue	400 ml + 100 gr	24

6–STORAGE AND SHELF LIFE

12 months in unopened packaging in a dry and cool storage place at temperatures between +5°C and +25°C.

7- RESTRICTIONS;

- Cyanoacrylates should ideally be stored in original sealed containers until used.
- Avoid exposure to strong light and heat sources
- Cyanoacrylates can bond to skin within seconds
- Do not drip into skin or into eyes - can cause serious injury to your eyes.
- Will become hard in container if not closed properly!
- Activator is flammable. Do not throw into fire. Do not inhale.
- Activator box is pressured. Do not crush or drill.

8-TECHNICAL PROPERTIES

Glue

Basis	: Ethyl Cyanoacrylate	
Appearance	: Liquid gel	
Color	: Colorless	
Application Temperature	: +5°C to +35°C	
Density	: 1.06 ± 0.01 gr/cm ³	ASTM D1875
Flashpoint	: >81°C	
Viscosity	: 1200 - 1800 Cps at 25°C	ASTM D1084
Temperature Resistance	: -20°C to +70 °C	

Activator

Basis	: Hexane	
Appearance	: Aerosol	
Color	: Colorless	
Application Temperature	: +5°C to +35°C	
Temperature Resistance	: -20°C to +70 °C	

DISCLAIMER

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

SUF-FIX