

SUF-FIX 112 LEAKFIX SPRAY MEMBRANE

1 – PRODUCT DESCRIPTION

SUF-FIX 112 is a rubber content protective coating spray that can be used to fill and seal leaks and cracks. It provides a waterproof, flexible sealing film. One can of Suf-Fix 112 can treat 2-8 square feet depending on the coating thickness needed. Once dry, the area sprayed can be painted any color. Suf-fix 112 forms a watertight flexible coating that will not drip, crack, peel or sag for years.

2 – APPLICATION AREAS

- Used for repairing hard-to-reach areas such as niches, corners, edges.
- It is used in the repair of coatings on the underbody of the vehicle.
- For interior trim of doors, trunk lids, etc. It is used to eliminate the noise.
- Used for watertightness in pipes, plumbing, gutters, roofs, terraces.

3 – PRODUCT FEATURES

- It is a rubberized protective coating that can be used to fill and seal leaks, cracks.
- It does not contain bitumen, it is a rubber-based resin.
- After complete drying, it forms an adhesive, flexible protective coating and is resistant to even the highest atmospheric and mechanical loads (eg stone strike).
- It can be painted over.
- Noise reduction effect.
- High resistance to abrasion.
- Fast drying (2-4 hours)
- Suitable for all common surfaces.
- Resistant to aging.
- Permanent elasticity.
- Strong adhesion.

4- INSTRUCTION

- The surfaces must be free of dust, oil and rust and must be dry.
- Loose parts at the bottom, if any, should be removed to prevent rusting.
- Make sure that the package is at room temperature before application.
- Shake vigorously for 2 minutes until the agitator ball sound is heard.
- Spray the surface to be applied in thin vertical/horizontal layers, 2-3 coats, from approximately 30 cm, and let it dry for a short time.

5-TECHNICAL SPECIFICATIONS

Parameter	Value
Appearance	Liquid
Colour	Black, White, Transparent
Application Thickness	400-500 μm
Drying Time	2-4 HOURS
Application Temperature	15 °C / 25 °C
Temperature Resistance	-25 °C / 80 °C
Storage Temperature	10 °C / 20 °C
Density	0.8 g/cm ³

6- SHELF LIFE AND STORAGE CONDITIONS

- It is suitable for 24 months from the date of production when stored correctly between +10° C and +20 ° C in original,

7-PACKAGING

500 ml-400 ml

8- COLOR VARIETIES

Transparent ,White and Black