



SUF-FIX 200 ARTIFICIAL GRASS ADHESIVE

Polyurethane Adhesive for Artificial Grass

Product Description

Suf-Fix PU 200 is a solvent-free two component polyurethane based adhesive.

Properties

- Durability against humidity, water and most of the chemicals especially acid rains
- Resistant against tough climatic changes
- Permanent adhesion
- High mechanical properties
- Strong adhesion to artificial grass, seaming (jointing) tapes
- Thixotropic flow behaviour
- Solvent free
- Easy to apply
- Flexible

Application Areas

It is used in bonding artificial grass carpet to jointing tapes in indoor and outdoor applications.

Application Instructions

The resin component A should be thoroughly stirred to incorporate any slight separation, whilst continuing stirring the contents of the hardener component B should be added. Continue stirring until a homogeneous mix is obtained. The mixed material must be used within 30 minutes of mixing at 20°C. The surface must be dry and clean.

Technical Properties

Mixing Ratio	7 : 1 (By weight)
Density of mixture (20°C)	app. 1,80±0.1 gr/cm ³
Density of Comp. A (20°C)	app. 2,90±0.1 gr/cm ³
Density of Comp. B (20°C)	app. 1,22±0.05 gr/cm ³
Pot-life (23°C)	30-40 min.
Application temperature	Min 5°C
Curing (20°C and %60 relative humidity)	6 hours
Colour and odour	Green, Odorless

Consumption

0,20 kg – 0,25 kg is used per mt/jointing tape

Storage

1 year under standard room conditions. Products should remain in their original, unopened packages.

Packaging

13 KG, 24 KG Bucket (A+B)

Important Notes

Substrate must be dry, clean, and free from dust, grease and oil. Application must be done between 5°C and 30 °C.

Cautions

Harmful if swallowed. Seek immediately medical attention. Rubber gloves and safety glasses with side guards should be worn.

DISCLAIMER

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.